

	Product Name	120W HiRack LED Linear High Bay	
	Item No.	HDLED120/SWE	
Optical Data			
LED Type	Nichia SMD	CCT	5000K
System Efficacy	135(±5%)lm/W(5000K Ra70)	CRI	Ra70, Ra80
Luminous Flux	16200(±5%)lm(5000K Ra70)	Beam Angle	L02801, L02802, L02803, L02804, L02805
Electrical Data			
Power Supply	Mean Well	Power Frequency	50/60Hz
Input Voltage	AC100-240V / AC100-277V	Power Factor	>0.92
Input Surge Protection	2kV line-line, 4kV line-earth		
Others			
System Power Consumption	120±6W	Storage Temperature	-20°C to +60°C(-4°F to +140°F)
Housing	Aluminum Alloy	Operating Temperature	0°C to +40°C(32°F to +104°F)
Ingress Protection	IP20	Operating Humidity	15-90%RH
LED Life Span	>50,000Hrs(Ta=30°C@L70)	Luminaire Net Weight	7.5±0.3kg (16.53±0.66Lbs)
Outlook Dimensions	949×137×162mm (37.36"×5.39"×6.38")	Carton Size	1020x 200 x 210mm (40.16"×7.87"×8.27")
Battery	4000mAh 12.6V	Battery Duration	3hours(10W)
Luminous Efficacy	150LM/W(CCT=5000K)	Warranty (Emergency Driver)	1 year
Protection Class	Class I		
Certification			
Optional Info.			
Installation Method	Wire Suspension Installation / Ceiling Mounting		
Battery	10 W		
Intelligent Control			
Physical Dimensions		Light Distribution Curve	
			